



**TAMA**®

**AIR FILTRATION  
I B E R I C A**

## DUCTING AND COMPONENTS



To completion of the whole supply, Tama offers a wide range of zinc-coated sheet steel pipes and fittings of various sizes and thicknesses, available in the catalogue.

## DUCTING AND COMPONENTS



### PIPES

Realized in zinc-coated steel sheet, with lengths from 1 m and 1.5 m. Sheet thicknesses from 6/10 to 10/10 with  $\varnothing$  80 mm to 1000 mm. Available in smooth, flapped or flanged version.



### CIRCULAR CURVE 30, 45, 60, 90 WITH SECTORS

Realized in zinc-coated steel sheet, sheet thicknesses 8/10 with  $\varnothing$  from 80 mm to 1000 mm. Available in smooth, flapped or flanged version.



### 1-WAY DEVIATION

Realized in zinc-coated steel sheet, with  $\varnothing$  from 80mm to 1000 mm. Available in smooth or flapped version.



### CONNECTOR

Realized in zinc-coated steel sheet, sheet thicknesses from 8/10 to 15/10 with  $\varnothing$  from 80mm to 1000 mm. Available in smooth, flanged or flapped version.



### CONE

Realized in zinc-coated steel sheet, sheet thicknesses from 8/10 to 15/10 with  $\varnothing$  from 80mm to 1000 mm. Available in smooth or flapped version.



### 4/5/6/7 HEADED OUTPUT

Realized in zinc-coated steel sheet, sheet thicknesses from 8/ with  $\varnothing$  from 180mm to 400 mm. Available in smooth, flanged or flapped version.



### EXPULSION CAP WITHOUT TOP

Realized in zinc-coated steel sheet, sheet thicknesses from 8/10 to 15/10 with  $\varnothing$  from 200mm to 1000 mm. Available in smooth or flapped version.



### EXPULSION CAP WITH MESH

Realized in zinc-coated steel sheet, Sheet thicknesses from 8/10 to 15/10 with  $\varnothing$  from 80mm to 1000 mm. Available in smooth, flanged or flapped version.



### CHINESE STYLE EXPULSION CAP

Realized in zinc-coated steel sheet, Sheet thicknesses from 8/10 to 15/10 with  $\varnothing$  from 120mm to 1000 mm. Available in smooth or flapped version.



### SOUNDPROOFING TUBE

Realized in zinc-coated steel sheet, with lengths from 1 m and 1.5 m. sheet thicknesses from 8/10 to 10/10 with  $\varnothing$  80 mm to 1000 mm. Available in smooth, flanged or flapped version.



#### CIRCULAR AND LINEAR SOCKET

Realized in zinc-coated steel sheet, sheet thicknesses from 8/10 to 10/10 with  $\emptyset$  from 80 mm to 1000 mm. Available in smooth or flapped version.



#### ANTI-VIBRATION JOINT with PVC CANVAS

Realized in zinc-coated steel sheet, sheet thicknesses from 6/10 with  $\emptyset$  from 100 mm to 1000 mm. Available in smooth, flanged or flapped version.



#### CIRCULAR STOPPER

Realized in zinc-coated steel sheet, with  $\emptyset$  from 80mm to 1000 mm.



#### CLAMPS

Clamp for tubing, widths from 300 mm to 1400 mm.  
Painted clamp for chimney,  $\emptyset$  from 300 mm to 1000 mm.



#### COLLARS:

##### PAINTED COLLAR

Realized in painted steel sheet,  $\emptyset$  from 300 mm to 1000 mm.

##### ZINC-COATED STEEL SHEET COLLAR

Collar realized in zinc-coated steel sheet,  $\emptyset$  from 80 mm to 400 mm.

##### MONO-COLLAR

Realized in zinc-coated steel sheet,  $\emptyset$  from 180 mm to 1000 mm.



#### FLANGES:

##### CIRCULAR PRESSED FLANGE

Realized in zinc-coated steel sheet,  $\emptyset$  from 80 mm to 600 mm.

##### CIRCULAR ANGULAR FLANGE

Realized in zinc-coated steel sheet,  $\emptyset$  from 80 mm to 600 mm.



#### GUILLOTINE SHUTTERS:

##### HAND GUILLOTINE SHUTTER

Light range:  $\emptyset$  from 80 mm to 600 mm.  
Heavy-duty range:  $\emptyset$  from 350 mm to 800 mm.

##### PNEUMATIC GUILLOTINE SHUTTER

Light range:  $\emptyset$  from 80 mm to 300 mm.  
Heavy-duty range:  $\emptyset$  from 350 mm to 800 mm.

##### ELECTRO-PNEUMATIC GUILLOTINE SHUTTER

Light range:  $\emptyset$  from 80 mm to 300 mm.  
Heavy-duty range:  $\emptyset$  from 350 mm to 800 mm.  
Realized in zinc-coated steel sheet, available in smooth, flanged or flapped version.



#### HAND, PNEUMATIC AND ELECTRO-PNEUMATIC BUTTERFLY SHUTTER

Realized in zinc-coated steel sheet,  $\emptyset$  from 80 mm to 600 mm.  
Available in smooth, flanged or flapped version.



#### NON RETURN VALVE

Realized in zinc-coated steel sheet,  $\emptyset$  from 200 mm to 600 mm.  
Available in smooth, flanged or flapped version.



#### FLOOR SUCTION OPENING

Realized in zinc-coated steel sheet,  $\emptyset$  from 120 mm to 150 mm.  
Available in smooth, flanged or flapped version.



#### FLEXIBLE HOSE

Realized in strengthened and transparent polyurethane with steel spiral.



#### FLEXIBLE HOSE CLAMP

Realized in zinc-coated steel sheet,  $\emptyset$  from 60 mm to 400 mm.